

Dr. Fixit Fibre Mesh



REINFORCING GLASS FIBRE MESH FOR PLASTERS, RENDERS AND WATERPROOFING COATINGS

Description

Dr. Fixit Fibremesh is an alkali resistant woven fiberglass mesh suitable as reinforcement for various plaster and render application.

Uses

Dr. Fixit Fibremesh is ideal for reinforcing plaster or render, particularly around openings or areas of traditional weakness. It can be used to stabilize unstable surfaces, cover and help prevent cracking. It is a flexible lattice made from special woven glass-fiber strands offering incredible strength when embedded into wet basecoat plaster or render. It is used to reinforce gypsum plaster and waterproof in place where low tear strength are sufficient.

Advantages

- o Versatile -Compatible with all major plasters and renders.
- o It is light weight and can be handled easily.
- o Easy to use - cut to size with a knife or scissors.
- o Tear and Alkali resistant.
- o Flexible and easily applied on curved surface

PROPERTIES	Value
Colour	Offwhite and Various
Form	Roll
Weight (approx.)	70 GSM
Mesh	2x2 mm

Compatibility

Dr. Fixit Fibremesh can be used with various cements and gypsum based plasters.

Application

Follow the project specification and guidelines. Below guidelines can be followed as a standard practice.

- o Mesh must overlap by a minimum of 100 mm.
- o Mesh upstand and downturn at openings to be a minimum of 300 mm.
- o Mesh to be extended past openings a minimum of 500 mm.
- o Solid band areas of block work between windows and doors to be fully meshed.

Pack Size: Roll 1 x 50 meter

Storage: Store in a dry condition and in shade.

Health and safety Precautions

Dr. Fixit Fibremesh may liberate fine dust while cutting. Ensure suitable dust masks are worn in addition to all standard PPE.



DR. FIXIT offers a wide range of Structural Protection and Waterproofing systems:



WATERPROOFING



CONCRETE &
STRUCTURAL REPAIR



CRACKFILL &
SEALANTS



BONDING AGENTS



SURFACE PLASTERS



GROUTS & ANCHORS



MORTARS



MARBLE & STONE
PROTECTION



PERFORMANCE
FLOORING



UNDERLAYMENTS



SPECIALITY
CONSTRUCTION
PRODUCTS



TILE ADHESIVES
& GROUTS



Pidilite MEA Chemicals LLC

PO Box 120657

Dubai, United Arab Emirates

T +971 4 884 9880 F +971 4 884 9879

Web: www.pidilitemea.com

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products