

Dr. Fixit Primeseal - AE



HIGH OPACITY PRIMER FOR WALL COATING

Description

Dr. Fixit Primeseal-AE is a priming coat for the Dr. Fixit range of high performance acrylic and anti-carbonation coatings.

Typical Applications

- Priming of plastered walls, concrete, brickwork, masonry and blockwork etc.

Features

- Excellent adhesion to dusty or porous substrates.
- Suitable for internal and external applications.
- Suitable for use on high alkaline substrates.
- Provides excellent efflorescence resistance.

Packaging

5 and 20 Litres

Method of Application

1 SURFACE PREPARATION

- Substrates must be free from laitance, loose material, oil, grease etc.
- All surface repairs and crack filling must be carried out using a suitable Dr. Fixit repair mortar.

2 APPLICATION

- Apply a single coat of Dr. Fixit Primeseal-AE on the cleaned substrate & allow it to dry for 2 to 3 hours. If required subsequent coats should be applied after 2 hours at 30°C before applying finish coats.

Note:

- Do not dilute.
- Substrate must be surface dry.
- Do not apply during rain or in direct sunlight.

Technical Information

PERFORMANCE PROPERTIES	TEST RESULTS
Specific Gravity at 30°C	1.25 ± 0.02
Intercoat Interval	1 - 2 hours

Theoretical Coverage

0.1 - 0.125 ltr/sq.mt

Storage

When stored in dry conditions out of sunlight in original unopened packaging this product has a shelf life of 12 months. Storage above 35°C will reduce shelf life and product performance.



Health and Safety

This product is a water based emulsion of non-hazardous polymer. It is non-flammable and essentially non-toxic. Normal industrial hygiene procedures should be adhered to particularly when spraying and it is recommended that gloves and eye protection be worn. In case of skin or eye contact, thoroughly irrigate with water and seek medical advice if any irritation develops or persists. In the case of accidental ingestion, wash mouth out with water and seek medical attention. Spillages should be cleaned up immediately with water as they will leave a film on evaporation. See MSDS for further information.

Pidilite MEA Chemicals L.L.C offers a wide range of Structural Protection and Waterproofing systems:



WATERPROOFING



CONCRETE & STRUCTURAL REPAIR



CRACKFILL & SEALANTS



BONDING AGENTS



SURFACE PLASTERS



GROUTS & ANCHORS



MORTARS



MARBLE & STONE PROTECTION



PERFORMANCE FLOORING



UNDERLAYMENTS



SPECIALITY CONSTRUCTION PRODUCTS



TILE ADHESIVES & GROUTS



Pidilite MEA Chemicals LLC

PO Box 120657

Dubai, United Arab Emirates

T +971 4 884 9880 F +971 4 884 9879

Web: www.pidilitemea.com

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.