

RoK Thinners No.1 (formerly Dr Fixit Resin Cleaner)



VISCOSITY REDUCING SOLVENT AND TOOL CLEANER

Description

RoK Thinners No. 1 is designed for the addition to resin coatings to aid substrate penetration and for cleaning tools and injection equipment contaminated with epoxy and polyurethane resins and grouts.

Typical Applications

- The dilution of resin primers and coatings
- The cleaning of tools contaminated with uncured polyurethane and epoxy resins.
- Cleaning and flushing of liquid uncured epoxy and polyurethane from injection pumps and lines.
- The removal of spilled material.

Packaging

20 Litres

Method of Application

- When diluting always add after the initial mixing of resin and curing agent.
- Always clean equipment before the resin has set.
- Tools can be immersed prior to wiping with a clean cloth or scrubbed with a brush.
- Injection equipment must be purged of all excess resin prior to flushing with RoK Resin Cleaner.
- Waste must not be discharged into sewage systems. Always dispose of according to local regulations.

Note:

- Keep containers closed when not in use.
- Avoid spillage and dispose of all containers and cleaning cloths.
- Apply only in well ventilated areas; provide adequate ventilation or air evacuation at working areas.

Storage

When stored in dry conditions out of sunlight in original unopened packaging this product has a shelf life of 12 months. Storage above 35°C will reduce shelf life and product performance.

Health and Safety

- Highly flammable.
- As with all chemical products, caution should always be exercised. Protective clothing such as gloves and goggles should be worn
- Treat any contact to the eyes or skin with fresh water immediately. Should any of the product be accidentally swallowed do not induce vomiting but call for medical assistance immediately.
- Ensure the pack is available for the medical attendant to examine any relevant instructions and content detail.
- Re-seal all containers after use and ensure product is stored as instructed.
- Do not smoke when handling this product.
- Do not inhale.
- Use in well ventilated areas and away from naked flames.

TECHNICAL DATA

Density	0.85
Viscosity @ 20°C	1 cps
Flash Point °C	15°C

RoK Thinners No.1 (formerly Dr Fixit Resin Cleaner)



VISCOSITY REDUCING SOLVENT AND TOOL CLEANER

Pidilite MEA Chemicals L.L.C offers a wide range of structural protection and waterproofing systems:



WATERPROOFING



CONCRETE &
STRUCTURAL REPAIR



CRACKFILL &
SEALANTS



BONDING AGENTS



SURFACE PLASTERS



GROUTS & ANCHORS



MORTARS



MARBLE & STONE
PROTECTION



PERFORMANCE
FLOORING



UNDERLAYMENTS



SPECIALITY
CONSTRUCTION
PRODUCTS



TILE ADHESIVES
& GROUTS



Pidilite MEA Chemicals LLC
PO Box 120657
Dubai, United Arab Emirates
Tel: +971 4 884 9880
Fax: +971 4 884 9879
Web: www.pidilitemea.com

Disclaimer: The product information & application details given by the company & its agents have been provided in good faith & meant to serve only as general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problem, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee/warranty as to the other results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products